

DOUBLE ENDED HALOGEN LAMPS

100-1500 Watt * 120, 130, 208, 22, 240 & 277 Volt



- **Long Life**
Less frequent re-lamping reduces maintenance costs
- **Heavy Gauge Glass & Connections**
Commercial grade lamps for long term durability and reliability
- **Compact Size**
Fits more applications
- **Corrosion Resistant Pins**
Promotes long, reliable life



Selection. Solutions. Simplicity.

23220 W. 84th St., Shawnee, KS 66227 • Ph: 1.800.852.2217 • Fax: 1.913.441.6679 • Email: eiko@eiko.com
EiKO CANADA: 81 King Street, Barrie, ON L4N 6B5, Canada • Ph: 705-721-5189 • Fax: 705-721-7855

www.eiko.com

Double Ended Halogen Lamps								
Ordering Code	Watts	Volts	Shape	Base	Filament	MOL	MOD	Life Hours
Q100T3/CL/120V	100	120	T-3	Recessed Single Contact (R7s)	CC-8	4.69/119.1	0.40/10.0	2000
Q150T3/CL/120V	150	120	T-3	Recessed Single Contact (R7s)	CC-8	4.69/119.1	0.40/10.0	2000
Q250T3/CL/120V	250	120	T-3	Recessed Single Contact (R7s)	C-8	4.69/119.1	0.40/10.0	2000
Q300T3/CL/120V	300	120	T-3	Recessed Single Contact (R7s)	C-8	4.69/119.1	0.40/10.0	2000
Q300T3/CL/130V	300	130	T-3	Recessed Single Contact (R7s)	C-8	4.69/119.1	0.40/10.0	2000
Q300T3/CL/220V	300	220	T-3	Recessed Single Contact (R7s)	C-8	4.69/119.1	0.40/10.0	2000
Q300T3/CL/240V	300	240	T-3	Recessed Single Contact (R7s)	C-8	4.69/119.1	0.40/10.0	2000
Q500T3/CL/120V	500	120	T-3	Recessed Single Contact (R7s)	C-8	4.69/119.1	0.40/10.0	2000
Q500T3/CL/130V	500	130	T-3	Recessed Single Contact (R7s)	C-8	4.69/119.1	0.40/10.0	2000
Q500T3/CL/220V	500	220	T-3	Recessed Single Contact (R7s)	C-8	4.69/119.1	0.40/10.0	2000
Q500T3/CL/240V	500	240	T-3	Recessed Single Contact (R7s)	C-8	4.69/119.1	0.40/10.0	2000
Q750T3/CL/120V	750	120	T-3	Recessed Single Contact (R7s)	C-8	7.50/190.5	0.40/10.0	2000
Q750T3/CL/240V	750	240	T-3	Recessed Single Contact (R7s)	C-8	7.50/190.5	0.40/10.0	2000
Q1000T3/CL/120V	1000	120	T-3	Recessed Single Contact (R7s)	C-8	10.06/255.6	0.40/10.0	2000
Q1000T3/CL/220V	1000	220	T-3	Recessed Single Contact (R7s)	C-8	10.06/255.6	0.40/10.0	2000
Q1000T3/CL/240V	1000	240	T-3	Recessed Single Contact (R7s)	C-8	10.06/255.6	0.40/10.0	2000
Q1000T3/CL/277V	1000	277	T-3	Recessed Single Contact (R7s)	C-8	10.06/255.6	0.40/10.0	2000
Q1500T3/CL/120V	1500	120	T-3	Recessed Single Contact (R7s)	CC-8	10.06/255.6	0.40/10.0	2000
Q1500T3/CL/208V	1500	208	T-3	Recessed Single Contact (R7s)	C-8	10.06/255.6	0.40/10.0	2000
Q1500T3/CL/220V	1500	220	T-3	Recessed Single Contact (R7s)	CC-8	10.06/255.6	0.40/10.0	2000
Q1500T3/CL/240V	1500	240	T-3	Recessed Single Contact (R7s)	CC-8	10.06/255.6	0.40/10.0	2000
Q1500T3/CL/277V	1500	277	T-3	Recessed Single Contact (R7s)	CC-8	10.06/255.6	0.40/10.0	2000

NOTES: