Wireless PresentationPro™



Model PA329

OF EDUCATION

School audio equipment needs to be rugged and versatile, whether it's needed inside or outdoors, hooked up to a computer, projector, smartphone or tablet, or needed for straight forward voice amplification.

The variations are endless and the flexibility built into the PresentationPro makes this PA workhorse a good investment. It's built for fast and easy set-ups so you don't need an

Shown with optional MB-PA3W mounting bracket

engineering degree in order to turn it on and start the presentation.



With an increasing number of schools installing projectors and interactive whiteboards into classrooms on a district wide basis, the need has never

been clearer to complement these systems with a high-quality speaker that engages students. And with

students being involved in so many technology-based activities throughout the year, including Skype sessions Google Hangouts, Facetime, and podcasting, having a powerful enough speaker in the classroom is essential.

> Tripod mounts directly into the underside of the PresentationPro



The PresentationPro provides educators with high-quality audio support, whether for vocal reinforcement or connecting to mobile devices, LCD projectors, netbooks, notebooks, laptop & desktop computers for enhanced audio

learning. This way the entire class can hear the video

or any other digital resource being used.

The PresentationPro is powerful enough so a single speaker can be used in each classroom, minimizing installation time and costs.

It can be used in classrooms, labs, cafeterias, auditoriums, meeting rooms, hotel & conference rooms, and even outdoor events.



Optional MB-PA3T holds the power supply when the PresentationPro is used on a tripod



Wireless PresentationPro™

Model PA329

THE SIGHTS & SOUNDS OF EDUCATION

- 1. Rugged steel-reinforced handle for easy mobility
- 2. Volume up / Mute / Volume down controls
- 3. Volume inidicator
- 4. Power switch, LED indicator & DC power input jack
- 5. PI-RC Remote controls volume up / down, mute, speaker power and magnetically rests on top of speaker when not in use
- 6. Separate bass, treble controls for quality sound
- 7. 1/4" Line in and line out connect with LCD projectors. computers, whiteboards
- 8. RCA & 3.5mm Aux in jacks connects with mobile devices
- 9. XLR and 1/4" mic inputs
- 10. LED displays wireless mic channel, RF & audio signals, with channel up/down adjustments
- 11. Set button to sync wireless channel with transmitting mic
- 12. Microphone volume control
- Ideal for mobile presenters, classroom and athletic uses
- Includes volume/mute remote control
- Warranty for school use unlike some other audio products purchased from consumer electronics stores whose warranties would be voided if used in schools voided if used in schools

"Project Intercept"

Please contact us immediately if you experience any difficulties with your PA329. Our "Project Intercept" customer service program will quickly repair or replace items under warranty. Simply contact us via phone or email warranty@califone.com

Visit our website to register your product and to learn more about the complete line of Califone® audio enhancing and visual technology products including: Wired and Wireless public address systems, microphones, headphones & headsets, group listening centers, multimedia players, computer peripherals, installed infrared systems.

We are proud of helping teachers enhance student understanding and achievements since 1947, with your satisfaction as our first priority.

The PresentationPro carries a six-vear warranty and service support available through authorized dealers nationwide.

Distributed by:



Specifications

Rated Power Output: 30 watts RMS Sensitivity for Rated Output: Line:125 mVrms

> Microphone: 4 mVrms Auxiliary: 250 mVrms 60 Hz - 20 kHz ± 3dB

Dispersion Angle: 90° H x 120° V Speaker: 6.5" full-range speaker

Distortion 1% (at 10W)

Frequency Response:

Crossover: L/C - 6dB/Octave @ 4 kHz Inputs:

Line inputs: Hi-Z, RCA (summing L+R) Balanced mic: Hi or Lo-Z, with phantom power (+15 volts D.C.)

Unbalanced mic:Lo -Z, 1/4"-phone Aux In: Hi-Z Mono 1/4"-phone and single 3.5mm stereo

UHF Receiver Specifications Carrier Frequencies: 904 - 925 mHz

Channels:

#1 904.85, #2 905.75, #3 906.85, #4 908.15,

#5 909.65, #6 911.35, #7 913.45, #8 914.85, #9 915.75, #10 916.85, #11 918.15, #12 919.65, #13 921.35, #14 923.25, #15 924.15, #16 925.3

Line Output: 250mv constant

Remote Control 20' range with 45 degree operating

field in front of the speaker

AC Power Requirements: 110 - 125 VAC, 50/60 Hz or 208 - 240 VAC, 50/60 Hz

Dimensions (HWD): 6.25" x 10" x 8.5"

Weight: 10 pounds, shipping weight 13 lbs. Carton (2 units) 20 pounds, shipping weight 28 lbs. 6 year from date of purchase for Warranty

use in school, business, church and

government facilities

CPSIA Click here to view the safety

compliances for this product under the Consumer Product Safety

Improvement Act

Califone® International Inc. 800, 722-0500 califone.com