UC-MM30-TA

- *Tabletop audio conferencing solution for Microsoft Teams® Rooms environment*
- *Native Microsoft Teams Rooms touch screen UI provides a consistent user experience with simple operation and one-touch meeting joins*
- *Complete kit contains the Crestron Tabletop conference device and PoE injector— just add a mount*
- *Easy to specify and install — no custom design, programming, or software installation required*
- *Network management and provisioning, system alerts, and the pairing of the Crestron Flex tabletop conference device to the system's UC Engine through the XiO Cloud® service*
- *Enterprise-grade security - connects and communicates securely over any enterprise or SMB network*
- *Dual-band Wi-Fi® connectivity*
- *Supports a single video display*

The Crestron Flex UC-MM30-TA system provides an audio conference room solution for use with the Microsoft Teams Rooms intelligent communications platform. It features a Crestron Flex tabletop conference device (UC-2).

Native Microsoft Teams® Rooms Experience

The UC-MM30-TA system brings the full Microsoft Teams Rooms UC experience to any meeting space in an enterprise or SMB facility.

Intuitive User Interface with Impressive Audio

With a large 7 in. HD color touch screen and an integrated AEC-enabled USB speakerphone that affords full-duplex wideband audio performance, the Crestron Flex Tabletop Conference device (UC-2) provides a superior conferencing and collaboration experience for meeting rooms, huddle spaces, and executive offices.

Enterprise-Grade Security

Crestron Flex is an enterprise-grade solution, engineered in partnership with Microsoft® to integrate seamlessly into any Microsoft Teams Rooms software deployment. Crestron Flex is ideally equipped for mass deployment throughout any sized corporate, university, medical, military, or government facility.

Easy Provisioning and Device Management

The XiO Cloud service is an IoT cloud based provisioning service that enables installers and IT managers to deploy and manage thousands of devices easily. The XiO Cloud service allows for system alerts, network management and provisioning, and the pairing of a control device to the system's UC Engine. System updates are controlled by Windows® software update.

Visit www.crestron.com/xiocloud for additional information.

Deployment Resources

View the Crestron Flex Pre-Deployment Checklist to help plan your Crestron Flex installation.

Specifications

Included Components

UC-2	Crestron Flex Tabletop Audio Conference System includes:

- PoE+ Injector, Input: 100~240 VAC, Output: 48 VDC, 0.5 A
- Cable, CAT5e, RJ45-to-RJ45, 12 ft (3.7 m) (x2)
- Cable, USB 2.0, A - Micro B, 5.8 ft (1.8 m)

Crestron Flex Tabletop Conferencing System

Touch Screen	7 in. (178 mm) diagonal capacitive multi-touch TFT active matrix color LCD, 1280 x 800 pixels
UI	Microsoft Teams Audio UI
Mic Mute Symbol and Light Bar	(4) Capacitive buttons with bi-color LEDs, toggles between mute and unmute
AEC	Automatic gain control, dynamic noise reduction, acoustic echo cancellation, full-duplex IEEE 1329 Type 1 compliant
Speaker	Full range speaker; Amplifier Power: 7 W (rated power); Output Volume: 83 ±3 dBA @1m 1 kHz; Frequency Response: 100 Hz - 20 kHz
Microphones	(4) Built-in omnidirectional, digital MEMS microphones with 360° audio pickup; Maximum pickup range: 10 ft (3 m) typical
Occupancy Sensor	Approx. 10 ft (3 m) PIR range in front of touch screen
Ethernet	10/100 Mbps, auto-switching, auto-negotiating, auto-discovery, full/half duplex, DHCP, TCP/IP, UDP/IP, CIP, SSL, TLS, SSH, SFTP (SSH File Transfer Protocol), SRTP, IEEE 802.1X, Active Directory® authentication, digest access authentication, password login, XiO Cloud client, Microsoft Intune® client, IEEE 802.3at Type 2 PoE+ compliant
Wi-Fi®	Dual-band 802.11a/b/g/n/ac (2.4 GHz & 5 GHz)
USB	USB 2.0 micro Type B device port, supports UAC for audio interface to UC Engine (cable included)
Power	IEEE 802.3af Class 3 and 802.3at Class 4 PoE+ powered device; PoE+ injector included
Dimensions	Height: 3.02 in. (77 mm) Width: 7.17 in. (182 mm) Depth: 9.61 in. (244 mm)
Weight	2.1 lb (0.96 kg)

Models

UC-MM30-TA
Crestron Flex Tabletop Audio Conference System for Microsoft Teams® Rooms Systems

UC-MM30-TA-I
Crestron Flex Tabletop Audio Conference System for Microsoft Teams® Rooms Systems, International

Available Accessories

UCA-SMK-UC2
Swivel Mount Kit for Crestron Flex Tabletop Conference Systems

SW-XIOC-EM
XiO Cloud® Provisioning and Management Service, Endpoint Management License

SW-XIOC-S
XiO Cloud® Provisioning and Management Service, Support License

SW-XIOC-API
XiO Cloud® Provisioning and Management Service, REST API License

Crestron Flex Tabletop Conferencing System (UC-2)

9.61 in.
(244 mm)

7.17 in.
(182 mm)

3.02 in.
(77 mm)